

PURION 1000 for water-disinfection

...is characterized by compact construction and a high degree of efficiency respecting to disinfection and energy consumption. The construction design follows laws, standards and regulations.



UV Plant PURION 2001 PVC is equipped with a PVC-U reactor. PURION 2001 PVC-U can be used to disinfect water up to a flow rate of 1.000 l/h and a transmission of at least 90% per cm. Other applications are pools or fish ponds up to a volume of 10.000 l at continuous recirculation.

The used UV-lamps are characterized by a long durability and a high degree of efficiency respecting to disinfection and energy consumption.

The power supply can be carried out with 230 V/50 Hz or optionally 12 V DC, 24 V DC or 110 V/60 Hz.

The compact construction design enables an easy replacement of the UV lamp at the end of their useful life.

You don't need any tool. Also replacement and cleaning of the quartz pipe can be arranged easily. UV disinfection is reached by floating the water through the reactor.

Inside the reactor an UV lamp enclosed in a UV-C transparent quartz pipe is surrounded by the drinking water to be treated. The small distance of 7,5 mm between the quartz pipe and the inner surface of the reactor ensures optimal irradiation and therefore optimal disinfection of the water.

manufacturer	PURION® GmbH
type	PURION 1000 PVC-U
flow rate	1 m³/h water
UVC-transmission	90% T ₁ cm
temperature of water	2°C to 30°C
reaktor	PVC-U
flange with adhesive sleeve	Ø 50 mm
seal	FPM
dimensions (L x Ø in mm)	420 x 42
distance flanges	280 mm
weight	2,8 Kg
life time of lamps	10.000 h
number of lamps	1
dose	400 J/m²
temperature max	30°C
max. working pressure	5 bar
protective system	IP 65
electrical connection	230 V/50 Hz or (optionally) 110-240 V 50/60 Hz 12 V DC or 24 V DC
total power	17 W
over current protection	10 A

This UV-plant is applied at:

Drinking water

Water of air conditioning

Disinfection of permeate

Pools

Aquariums

Fish ponds

Storm water of sewage plants

Pharmacy

Greenhouse

Water of domestic use

Advantages

- additional chemicals are not required for disinfection
- no change of hydro chemistry
- smell and taste of the water are not influenced by radiation
- installation in conveyor lines
- less required space
- manageable maintenance, small operation expenses