

PURION 2501 for water-disinfection

...is characterized by compact construction and a high degree of efficiency respecting to disinfection and energy consumption. The construction design follows laws, standards and regulations.



UV Plant PURION 2501 is equipped with a polished stainless steel reactor.

PURION 2501 can be used to disinfect pool water up to a Volume of 50.000 I and for a transmission of at least 90% per cm. To ensure the required transmission a preliminary filter could be necessary. Other applications are fish ponds up to a volume of 30.000 I at continuous recirculation.

The used UV-lamps are characterized by a long durability and a high degree of efficiency respecting to disinfection and energy consumption.

The power supply can be carried out with 230 V/50 Hz or 110 V/60 Hz.

The compact construction design enables an easy replacement of the UV lamp at the end of their useful life.

You don't need any tool. Also replacement and cleaning of the quartz pipe can be arranged easily. UV disinfection is reached by floating the water through the reactor.

Inside the reactor an UV lamp enclosed in a UV-C transparent quartz pipe is surrounded by the water to be treated.

The small distance of 27,5 mm between the quartz pipe and the inner surface of the reactor ensures optimal irradiation and therefore optimal disinfection of the water.

manufacturer	PURION® GmbH	
type	PURION 2501	
flow rate	14 m³/h	
	pools/ponds	
	up to 50.000 I	
UVC-transmission	90% T₁ cm	
temperature of water	8°C to 40°C	
reaktor	stl. steel 1.4571	
flanges external thread	R 1 1/2"	
seal	FPM	
dimensions (L x Ø in mm)	928 x 85	
distance flanges	810 mm	
weight	5,5 Kg	
life time of lamps	10.000 h	
number of lamps	1	
dose	300 J/m²	
temperature max	40°C	
max. working pressure	10 bar	
protective system	IP 65	
electrical connection	110-240 V 50/60 Hz	
(optionally)		
total power	90 W	
over current protection	10 A	

This UV-plant is applied at:

Drinking water		
Water of air conditioning		
Disinfection of permeate		
Pools	•	
Aquariums	•	
Fish ponds		
Storm water of sewage plants		
Pharmacy		
Greenhouse		
Water of domestic use		

Advantages

- additional chemicals are not required for disinfection
- no change of hydro chemistry
- smell and taste of the water are not influenced by radiation
- installation in conveyor lines
- less required space
- manageable maintenance, small operation expenses

